Samsung SCX-6345NJ + JScribe ليزر A4 1200 x 1200 نقطة لكل انش 1200 x الدفع لكل ألف

رمز المنتج SCX6345NJ : العلامة التجارية

SCX-6345NJ + JScribe : اسم المنتج





| Printing | | Paper handling | |
|---|------------------------|---------------------------------------|--|
| Print technology * | Laser | Maximum ISO A-series paper size * | A4 |
| Printing * | X | Paper tray media types * | Bond paper, Card stock, Envelopes, Recycled paper, Transparencies |
| Duplex printing * | ✓ | ISO A-series sizes (A0A9) * | A4, A5, A6 |
| Maximum resolution * | 1200 x 1200 DPI | ISO B-series sizes (B0B9) | B5 |
| Print speed (black, normal quality, A4/US Letter) * | 41 ppm | Non-ISO print media sizes | Folio, Statement |
| Warm-up time | 35 s | JIS B-series sizes (B0B9) | B5 |
| Time to first page (black, normal) | 8 s | Envelopes sizes | B5, C5, C6, DL |
| Copying | | Ports & interfaces | |
| Copying * | Mono copying | Standard interfaces | USB 2.0 |
| Maximum copy resolution * | 600 x 600 DPI | USB port | |
| Copy speed (black, normal quality, A4) | 43 cpm | USB 2.0 ports quantity | 1 |
| Maximum number of copies | 999 copies | Network | |
| Copier resize | 25 - 400% | Ethernet LAN * | ✓ |
| Scanning | | Performance | |
| Scanning * | Colour scanning | Internal memory * | 256 MB |
| Maximum scan resolution | 4800 x 4800 DPI | Sound pressure level (printing) | 60 dB |
| Scanner type * | Flatbed scanner | Sound power level (standby) | 43 dB |
| Scan technology | CCD | Mac compatibility | ✓ |
| Scan to Greyscale levels | FTP 256 | Design | |
| Fax | 250 | Market positioning * | Business |
| Faxing * | Mono faxing | Built-in display * | ✓ LCD |
| Modem speed | 33.6 Kbit/s | Display | LCD |
| Fax memory | 16 MB | Power | |
| Fax speed dialing (max numbers) | 200 | Power consumption (average operating) | 900 W |
| Fax speed (A4) | 3 sec/page | Power consumption (PowerSave) | 35 W |
| Features | | Power consumption (standby) | 170 W |
| Maximum duty cycle * | 200000 pages per month | Operational conditions | |
| Digital sender | X | Operating relative humidity (H-H) | 20 - 80% |
| Input & output capacity | | Operating temperature (T-T) | 10 - 32 °C |
| Total output capacity * | 500 sheets | Weight & dimensions | |
| Multi-Purpose tray | ✓ | Weight | 44.5 kg |
| Multi-Purpose tray input capacity | 100 sheets | Other features | |
| Auto document feeder (ADF) | ✓ | Dimensions (WxDxH) | 637.4 x 489 x 616 mm |
| Auto document feeder (ADF) input capacity | 50 sheets | Network ready | ✓ |
| | | | |

| Input & output capacity | | Other features | |
|-------------------------|------------|------------------------------|--|
| Maximum input capacity | 520 sheets | Compatible operating systems | Windows 98/Me/NT4.0/2000/XP/2003 Linux OS (Red Hat 8-9, Fedora Core 1-4, Mandrake 9.2-10.1, SuSE 8.2-9.2) Mac OS 8.6-9.2/10.1-10.4 |
| | | Emulations | PCL6, PostScript 3 |
| | | All-in-one functions | Copy, Fax, Scan |
| | | Colour all-in-one functions | Scan, No |

