Epson PowerLite Pro G5750WU 4500 ANSI Lumen LCD WUXGA (1920x1200) Weiß

Marke : Epson

Artikel-Code: V11H345020

Produktname : PowerLite Pro G5750WU

Epson PowerLite Pro G5750WU. Projektorhelligkeit: 4500 ANSI Lumen, Projektion Technologie: LCD, native Auflösung des Projektors: WUXGA (1920x1200). Light source type: Lampe, Service life of light source: 2000 h, Service life of light source (economic mode): 3000 h. Fokus: Manuell, Brennweitenbereich: 21.28 - 37.94 mm, Blendenbereich (F-F): 1,65 - 2,55. Analoges Signalformatsystem: NTSC, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM, Unterstützte Grafik-Auflösungen: 1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 640 x 480..., Unterstützte Video-Modi: 1080i, 1080p, 480i, 480p, 576i, 576p, 720p. Serielle Schnittstelle: RS-232, USB-Stecker: USB Typ-A



Ports & interfaces Projector Screen size compatibility * 762 - 7620 mm (30 - 300") Serial interface type * RS-232 Projection distance 0 - 14.9 m VGA (D-Sub) ports quantity * 1 Projector brightness * 4500 ANSI lumens HDMI ports quantity * 1 Projection technology * USB connector type USB Type-A LCD Projector native resolution * WUXGA (1920x1200) BNC input ports 1 1500.1 Contrast ratio (typical) * DVI port * Number of colours 16.78 million colours Network Horizontal scan range 15 - 92 kHz Ethernet LAN * 50 - 85 Hz Vertical scan range Ethernet LAN (RJ-45) ports 1 -20 - 20° Keystone correction, horizontal Ethernet LAN data rates 100 Mbit/s Keystone correction, vertical -30 - 30° Matrix type 3-panel (p-Si TFT active) Features Light source Noise level (economic mode) 33 dB 162 MHz Dot clock scanning frequency Light source type * Lamp Noise level * 39 dB Service life of light source * 2000 h Service life of light source Design 3000 h (economic mode) Product colour * White Lamp type UHF Cable lock slot 1 Lamp power 330 W Cable lock slot type Kensington Lens system Display Focus * Manual Built-in display * × Focal length range 21.28 - 37.94 mm 1.65 - 2.55 Aperture range (F-F) Power Zoom capability Power source * AC Manual Zoom type 477 W Power consumption (typical) * Optical zoom 1.x 10 W Power consumption (standby) * Throw ratio 1.3 - 2.36:1 100 - 240 V AC input voltage -9 - 9° Horizontal lens shift range 50 - 60 Hz AC input frequency Vertical lens shift range -58 - 58° **Operational conditions** Video Operating relative humidity (H-H) 0 - 40% NTSC, NTSC 4.43, PAL, PAL 60, PAL Analog signal format system * Weight & dimensions M, PAL N, SECAM Width 45.3 mm Full HD * X Depth 30 mm 1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1920 x 1080 (HD 1080), Height 14.6 mm Supported graphics resolutions 1920 x 1200 (WUXGA), 640 x 480 Weight *

(VGA), 800 x 600 (SVGA)

6.8 kg

Video		Packaging content	
Supported video modes	1080i, 1080p, 480i, 480p, 576i, 576p, 720p	Remote control included *	×
Ports & interfaces		Other features	
		Aspect ratio	16:10
S-Video inputs quantity	1	RS-232 ports	1
USB 2.0 ports quantity	1	Security features	cable hole, lens lock, lock provision

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.