Epson AcuLaser C2800N Colour 2400 x 2400 DPI A4

Brand: Epson Product code: C11CA09001BX

Product name: AcuLaser C2800N

AcuLaser C2800N

Epson AcuLaser C2800N Colour 2400 x 2400 DPI A4:

Combine speed and ease of use with superb colour and mono results. The Epson AcuLaser C2800 series brings value, reliability and laser quality to workgroup colour printing.

This is the perfect general purpose A4 colour laser for small work groups. Work quickly with a very fast first page out time and keep expenses down with a low cost per page. Integrate easily with a network interface, PCL and genuine Adobe® PS3 languages as standard.

This printer is easy to use, extremely reliable and simple to maintain. It's also very quiet when printing. And it's upgradable too, so you can add options such as a duplex unit as your business grows. Epson AcuLaser C2800N. Print technology: Laser, Colour. Maximum duty cycle: 60000 pages per month. Maximum resolution: 2400 x 2400 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 25 ppm, Duplex printing. Network ready



Printing		Performance	
Print speed (colour, normal quality, A4/US Letter)	20 ppm	Internal memory * Maximum internal memory	128 MB 640 MB
Colour *	/	Processor frequency	400 MHz
Print technology *	Laser	Sound pressure level (printing)	30 dB
Duplex printing *	✓	Sound power level (standby)	51 dB
Maximum resolution *	2400 x 2400 DPI	Design	
Print speed (black, normal quality, A4/US Letter) *	25 ppm	Certification	2006/95/EC EN60950-1, 2004/108/EC, EN 55022 Class B, EN
Warm-up time	30 s		55024, EN 61000-3-2; EN 61000-3-3
Time to first page (black, normal)	15 s	Power	
Time to first page (colour, normal)	15 s	Power consumption (standby)	78 W
Features		Power consumption (PowerSave)	17 W
Maximum duty cycle *	60000 pages per month	Operational conditions	
Input & output capacity		Operating temperature (T-T)	10 - 32 °C
Total input capacity *	250 sheets	Storage temperature (T-T)	0 - 35 °C
Total output capacity *	250 sheets	Operating relative humidity (H-H)	10 - 85%
Multi-Purpose tray	✓	Storage relative humidity (H-H)	15 - 80%
Multi-Purpose tray input capacity	150 sheets	Sustainability	
Maximum input capacity	950 sheets	Sustainability certificates	ENERGY STAR
Paper handling		Weight & dimensions	
Maximum ISO A-series paper size * ISO A-series sizes (A0A9) *	A4 A4, A5	Weight	24 kg
		Dimensions (WxDxH)	408 x 577 x 477 mm
ISO B-series sizes (B0B9)	B5	, ,	400 X 377 X 477 Hilli
Non-ISO print media sizes	Executive, Legal, Letter	Other features	
Media weight (tray 1)	60 - 216 gsm	Mac compatibility	✓
Network	,	Standard media sizes	(76.2 - 220 mm) x (98.4 - 355.6 mm)
Network ready Supported network protocols (IPv4)	TCP/IP: LPR, FTP, IPP, PORT2501, PORT9100, TCP/IP, NetBEUI TCP/IP: SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, mDNS†1, SNTP, SSDP, SLP, Auto-IP, SSDP MS, SNMP	Power requirements	220V - 240V ±10% / 50Hz, 60Hz ± 3Hz / 4.0 A
		Networking features	Ethernet 10/100 Base-TX
Management protocols		Power consumption (active)	730 W
		Compatible operating systems	Windows 2000 / XP / Server 2003 / Vista / XP x64 Edition / Server 2003 x64 / Vista x64 Mac OS 10.2.810.4.X,10.4.X
		Emulations	ESC/P-C, PCL5c, PCL6, APS3, PDF1.3, ESCP2, FX, I239X

Other features	
Stand-by LED	✓

