

DELL Latitude 7275 Intel® Core™ m7 m7-6Y75 Híbrido (2-en-1) 31,8 cm (12.5") Pantalla táctil 4K Ultra HD 8 GB LPDDR3-SDRAM 256 GB SSD Windows 10 Pro Checa, Eslovaco Negro

Marca : DELL Familia de productos: Código del producto: RPPXW Latitude

Nombre del producto: 7275

DELL Latitude 7275. Tipo de producto: Híbrido (2-en-1), Factor de forma: Convertible (extraíble). Familia de procesador: Intel® Core™ m7, Modelo del procesador: m7-6Y75, Frecuencia del procesador: 1,2 GHz. Diagonal de la pantalla: 31,8 cm (12.5"), Tipo HD: 4K Ultra HD, Resolución de la pantalla: 3840 x 2160 Pixeles, Pantalla táctil. Memoria interna: 8 GB, Tipo de memoria interna: LPDDR3-SDRAM. Capacidad total de almacenaje: 256 GB, Unidad de almacenamiento: SSD. Sistema operativo instalado: Windows 10 Pro. Color del producto: Negro






Software
Trial software Microsoft Office Operating system installed * Windows 10 Pro
Processor special features
Intel® Wireless Display (Intel®
WiDi)
Intel® My WiFi Technology (Intel®
Intel® Smart Response Technology ✓
Intel® Hyper Threading Technology (Intel® HT Technology)
Intel® Turbo Boost Technology 2.0
Intel® Small Business Advantage (Intel® SBA)
Enhanced Intel SpeedStep Technology
Intel® Clear Video HD Technology (Intel® CVT HD)
Intel Clear Video Technology
Intel® InTru™ 3D Technology
Intel® Insider™ ✓
Intel® Quick Sync Video Technology ✓
Intel Flex Memory Access
Intel® Smart Cache ✓
Intel® AES New Instructions (Intel® AES-NI)
Intel Trusted Execution Technology 🗸
Intel Enhanced Halt State
Intel VT-x with Extended Page Tables (EPT)
Intel® Secure Key ✓
Intel TSX-NI ✓
s

Виососки		Drogogov special factures	
Processor	CL I.I.	Processor special features	
Processor codename Bus type	Skylake OPI	Intel Stable Image Platform Program (SIPP)	✓
Stepping Stepping	D1	Intel® OS Guard	✓
Thermal Design Power (TDP)	4.5 W	Intel Software Guard Extensions	/
Configurable TDP-up	7 W	(Intel SGX)	•
Configurable TDP-down	3.5 W	Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT	✓
Tjunction	100 °C	for MID)	
Maximum number of PCI Express lanes	10	Intel 64	✓
PCI Express slots version	3.0	Execute Disable Bit	✓
PCI Express configurations	1x2+2x1, 2x2, 1x4, 4x1	Idle States	✓
ECC supported by processor	×	Thermal Monitoring Technologies	✓
Memory		Processor package size	20 X 16.5 mm
Internal memory *	8 GB	Supported instruction sets	SSE4.1, SSE4.2, AVX 2.0
Internal memory type	LPDDR3-SDRAM	Processor code	SR2EH
Memory clock speed	1600 MHz	CPU configuration (max)	1
Memory form factor	On-board	Embedded options available Graphics & IMC lithography	X 14 nm
Maximum internal memory *	8 GB	Intel Virtualization Technology for	
Storage		Directed I/O (VT-d)	✓
Total storage capacity *	256 GB	Intel Smart Response Technology	1.00
Storage media *	SSD	version Intel Stable Image Platform Program	
Number of SSDs installed	1	(SIPP) version	1.00
SSD capacity	256 GB	Intel Secure Key Technology version	1.00
SSD interface SSD form factor	SATA M.2	Intel Small Business Advantage (SBA) version	1.00
Optical drive type *	X	Intel TSX-NI version	1.00
Card reader integrated	^ /	Intel Virtualization Technology (VT-	·
Compatible memory cards	MicroSD (TransFlash)	x)	
	(Processor ARK ID	88199
			_
Graphics Discrete graphics card model *	Not available	Conflict-Free processor	✓
Discrete graphics card model *	Not available	Conflict-Free processor Battery	•
Discrete graphics card model * On-board graphics card *	✓	Battery Number of battery cells	2
Discrete graphics card model * On-board graphics card * Discrete graphics card *	×	Battery	
Discrete graphics card model * On-board graphics card *	✓	Battery Number of battery cells	2
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base	X Intel® HD Graphics Intel® HD Graphics 515	Battery Number of battery cells Battery capacity * Power AC adapter power	2 30 Wh
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency	✓ X Intel® HD Graphics	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency	2 30 Wh 30 W 50 - 60 Hz
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic	X Intel® HD Graphics Intel® HD Graphics 515	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM)	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T)	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T)	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T)	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone Camera	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓	Battery Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone Camera Front camera	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95%
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone Camera Front camera Front camera resolution (numeric)	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓ 5 MP	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% -15.2 - 3048 m
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone Camera Front camera Front camera resolution (numeric) Front camera resolution	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓ 5 MP 2592 x 1944 pixels	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% -15.2 - 3048 m
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone Camera Front camera Front camera resolution (numeric)	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓ 5 MP	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude Certificates	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio system Number of built-in speakers Speakers manufacturer Built-in microphone Camera Front camera Front camera resolution (numeric) Front camera resolution Video capturing speed	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓ 5 MP 2592 x 1944 pixels 30 fps	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude Certificates Certification Sustainability	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m
Discrete graphics card model * On-board graphics card * Discrete graphics card * On-board graphics card family On-board graphics card model * On-board graphics card base frequency On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card OpenGL version On-board graphics card ID Audio Audio Audio Audio Speakers manufacturer Built-in microphone Camera Front camera Front camera resolution (numeric) Front camera resolution Video capturing speed Auto focus	X Intel® HD Graphics Intel® HD Graphics 515 300 MHz 1000 MHz 1.74 GB 12.0 4.4 0x191E MaxxAudio Pro 2 Waves ✓ 5 MP 2592 x 1944 pixels 30 fps ✓	Number of battery cells Battery capacity * Power AC adapter power AC adapter frequency AC adapter input voltage AC adapter output current AC adapter output voltage DC-in jack Security Cable lock slot Cable lock slot type Trusted Platform Module (TPM) Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Certificates Certification	2 30 Wh 30 W 50 - 60 Hz 120 - 240 V 1.5 A 20 V Noble 0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m

Network		Weight & dimensions	
Wi-Fi	✓	Width	290.9 mm
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Depth Height	192.9 mm 17.1 mm
Ethernet LAN	×	Weight (tablet mode)	730 g
Bluetooth	✓	Width (tablet mode)	29.1 cm
Bluetooth version	4.1	Depth (tablet mode)	19.3 cm
Bluetooth Low Energy (BLE)	✓	Height (tablet mode)	8.1 mm
WWAN	Installed	Weight *	1.28 kg
Ports & interfaces		Packaging content	
DVI port	×	AC adapter included *	✓
Thunderbolt 3 ports quantity	2	Manual	✓
Combo headphone/mic port	/	Power cord included	✓
Docking connector	✓	Other features	
Keyboard		Maximum internal memory (64-bit)	8 GB
Pointing device	Touchpad	Intel segment tagging	Enterprise
Numeric keypad *	×	SIM card support	✓
Full-size keyboard	✓		
Windows keys	✓		
Keyboard language	Czech, Slovakian		
Software			
Operating system architecture	64-bit		



5397063923106

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.