

Fujitsu PRIMERGY TX200 S3 server Torn (4U) Intel® Xeon® 5000 Sequence 5110 1,6 GHz 1 GB DDR2-SDRAM 600 W

Brand : Fujitsu **Product family:** PRIMERGY **Product code:** VFY:TX200S3-002DE

2 x 0.5 GB. Optilise seadme tüüp: DVD-ROM. Toiteallikas: 600 W. Keretüüp: Torn (4U)

Product name: PRIMERGY

TX200 S3

Fujitsu PRIMERGY TX200 S3. Protsessori perekond: Intel® Xeon® 5000 Sequence, Protsessori sagedus: 1,6 GHz, Protsessori mudel: 5110. Sisemälu: 1 GB, Sisemälu tüüp: DDR2-SDRAM, Mälu (pesad x suurus):



Processor		Software	
Processor manufacturer * In Processor family * In Processor model * 55 Processor frequency * 1. Processor cores 2 Processor cache 4 Motherboard chipset In Thermal Design Power (TDP) 65 Processor cache type L2 Processor front side bus 10 Processor socket L6 Processor lithography 65 Processor threads 2 Processor operating modes 66 FSB Parity	Intel Intel® Xeon® 5000 Sequence 5110 1.6 GHz 2 4 MB Intel® 5000V 65 W L2 1066 MHz LGA 771 (Socket J) 65 nm 2 64-bit ✓ FSB	Compatible operating systems *	Microsoft Windows 2000 Server, Microsoft Windows 2000 Advanced Server, Microsoft Windows Server 2003 Enterprise Edition, Microsoft Windows Server 2003 Web Edition, Microsoft Windows Server 2003 Standard Edition, Microsoft Windows Small Business Server 2003 Standard Ed, Microsoft Windows Small Business Server 2003 Premium Ed, SuSE Linux Enterprise Server 8 for Intel x86, Red Hat Enterprise Linux 3, SuSE Linux Enterprise Server 9 - x86/AMD64/Intel EM64T, Microsoft Windows Server 2003 Standard x64 Edition, Red Hat Enterprise Linux 4, Microsoft Windows Server 2003 Enterprise x64 Edition, SuSE Linux 9.2, SuSE Linux 9.3, Red Hat Enterprise Linux 4 - Intel EM64T
Processor codename Tcase	Woodcrest 65 °C	Bundled software	ServerStart, ServerView
ECC supported by processor	×	Processor special features	
Execute Disable Bit Idle States Thermal Monitoring Technologies Processor package size Embedded options available Number of Processing Die Transistors CPU multiplier (bus/core ratio) Processing Die size Processor series Conflict-Free processor	7 7 37.5 x 37.5 mm x 291 M 6 143 mm² Intel Xeon 5100 Series x	Intel Rapid Storage Technology Enhanced Intel SpeedStep Technology Intel® Wireless Display (Intel® WiDi) Intel Virtualization Technology for Directed I/O (VT-d) Intel® Anti-Theft Technology (Intel® AT) Intel® Hyper Threading Technology (Intel® HT Technology) Intel® My WiFi Technology (Intel® MWT) Intel® Turbo Boost Technology	x
Memory		Intel® Quick Sync Video Technology	X
Internal memory * Internal memory type *	1 GB DDR2-SDRAM	Intel® InTru™ 3D Technology Intel® Clear Video HD Technology	× ×
ECC Memory layout (slots x size) Maximum internal memory *	✓ 2 x 0.5 GB 16 GB	(Intel® CVT HD) Intel® Insider™ Intel Flex Memory Access	× ×
Storage RAID levels	1	Intel® AES New Instructions (Intel® AES-NI)	×

Storage		Processor special features	
Optical drive type *	DVD-ROM	Intel Trusted Execution Technology	x
Network		Intel Enhanced Halt State	✓
Networking features	Gigabit Ethernet	Intel VT-x with Extended Page Tables (EPT)	×
Ports & interfaces		Intel Demand Based Switching	×
Ethernet LAN (RJ-45) ports *	1	Intel Clear Video Technology	×
USB 2.0 ports quantity PS/2 ports quantity VGA (D-Sub) ports quantity	3 2 1	Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID)	×
Serial ports quantity	2	Intel 64	✓
Design		Intel Virtualization Technology (VT-x)	✓
Chassis type *	Tower (4U)	Intel Dual Display Capable Technology	×
		Intel FDI Technology	×
		Intel Fast Memory Access	×
		Processor ARK ID	27214
		Power	
		Power requirements Power supply *	100 - 240 VAC, 50 - 60 Hz 600 W
		Weight & dimensions	
		Width Depth Height Weight	286 mm 775 mm 473 mm 25 kg
		Other features	
		Storage drive controller Dimensions (WxDxH) CD read speed	SAS 286 x 775 x 473 mm 48x

