Canon

Canon i-SENSYS MF8080Cw Laser A4 2400 x 600 DPI 12 ppm Wifi

Marque : Canon Famille de produit: i-SENSYS Code produit: 5119B021

Nom du produit : MF8080Cw

 $\label{eq:mf8080Cw} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 26kg, White} \mbox{MF8080Cw, Color Laser, 4-in-1, 8 ppm/12ppm(Colour/Mono), USB2.0, Fast Ethernet, 802.11 b/g, 802.1$

Canon i-SENSYS MF8080Cw. Technologie d'impression: Laser, Impression: Impression couleur, Résolution maximale: 2400 x 600 DPI, Vitesse d'impression (couleur, qualité normale, A4/US Letter): 8 ppm. Copier: Copie couleur, Résolution max. des copies: 600 x 600 DPI. Numérisation: Numérisation couleur, Résolution de numérisation optique: 600 x 600 DPI. Télécopier: Télécopie couleur. Taille de papier de série A ISO maximum: A4. Wifi. Couleur du produit: Blanc



	Paper handling	
600 x 600 DPI	Maximum ISO A-series paper size *	A4
Laser	Maximum print size	216 x 356 mm
Colour printing		Coated paper, Envelopes, Labels,
×	Paper tray media types *	Plain paper, Recycled paper, Transparencies
2400 x 600 DPI	ISO A-series sizes (A0A9) *	A4, A5
12 ppm	ISO B-series sizes (B0B9)	B5, B6
8 ppm	Non-ISO print media sizes Envelopes sizes	Executive, Statement 10, B5, C5, DL
30 s	Custom media width	76.2 - 215.9 mm
22 s	Custom media length	127 - 356.6 mm
28.5 s	Paper tray media weight	60 - 220 g/m²
	Auto Document Feeder (ADF) media weight	50 - 105 g/m²
×	Ports & interfaces	
Colour copying	Standard interfaces	Ethernet, USB 2.0, Wireless LAN
600 x 600 DPI		X
12 cpm	USB port	· ·
8 cpm	Network	
99 copies	Wi-Fi *	✓
25 - 400%	Ethernet LAN *	✓
	Wi-Fi standards	802.11b, 802.11g
×	Performance	
Colour scanning	Card reader integrated	×
600 x 600 DPI	Internal memory *	128 MB
9600 x 9600 DPI	Sound pressure level (printing)	63.4 dB
216 x 355 mm	Sound pressure level (copying)	63.4 dB
JPG, TIF	Sound pressure level (scanning)	63.4 dB
24 bit	Sound power level (standby)	43 dB
24 bit	Mac compatibility	✓
256	Design	
	•	White
×	Market positioning *	Business
	- p 3	
Colour faxing	Built-in display *	✓
Colour faxing 200 x 100 DPI	Built-in display *	✓ ICD
•	Built-in display * Display	✓ LCD
	Laser Colour printing X 2400 x 600 DPI 12 ppm 8 ppm 30 s 22 s 28.5 s X Colour copying 600 x 600 DPI 12 cpm 8 cpm 99 copies 25 - 400% X Colour scanning 600 x 600 DPI 9600 x 9600 DPI 126 x 355 mm JPG, TIF 24 bit 24 bit	Maximum ISO A-series paper size * Laser Colour printing X Paper tray media types * 2400 x 600 DPI ISO A-series sizes (A0A9) * 12 ppm ISO B-series sizes (B0B9) Non-ISO print media sizes 8 ppm Envelopes sizes Custom media width Custom media length Paper tray media weight Auto Document Feeder (ADF) media weight X Ports & interfaces Colour copying 600 x 600 DPI Company Standard interfaces Direct printing * USB port 8 cpm Network 99 copies Wi-Fi * 25 - 400% Ethernet LAN * Wi-Fi standards X Performance Colour scanning Card reader integrated 600 x 9600 DPI Internal memory * 9600 x 9600 DPI Sound pressure level (printing) 12 fx 355 mm Sound pressure level (scanning) 19 https://www.compatibility 12 bit Sound power level (standby) Mac compatibility

Fax		Power	
Fax memory Auto-redialing	, ,	Power consumption (average operating)	900 W
Fax speed dialing (max numbers) Fax forwarding Fax broadcasting 210 locations	Power consumption (standby) AC input voltage AC input frequency	15 W 220 - 240 V 50 - 60 Hz	
Error Correction Mode (ECM)		Operational conditions	
Fax dual access	✓	Operating relative humidity (H-H) Operating temperature (T-T)	20 - 80% 10 - 30 °C
Features		Weight & dimensions	
Maximum duty cycle * Digital sender Number of print cartridges * Printing colours * Page description languages	30000 pages per month X 4 Black, Cyan, Magenta, Yellow UFRII-LT	Width Depth Height Weight	430 mm 484 mm 429 mm 26 kg
Input & output capacity		Packaging content	
Total input capacity *	• • •	Drivers included	✓
Total output capacity *	125 sheets	Other features	
Paper input type Auto document feeder (ADF)		Networking features Dimensions (WxDxH)	Fast Ethernet, WLAN 430 x 484 x 429 mm
Auto document feeder (ADF) input capacity	50 sheets	Network ready	Windows 2000 Common 2002 Common
· · · · ·		Compatible operating systems	Windows 2000, Server 2003, Server 2008, Server 2008 R2, Windows XP, Windows Vista, Windows 7, Mac OS X 10.4.9- 10.7.x, Linux
		All-in-one functions	Copy, Fax, Print, Scan
		Colour all-in-one functions	Copy, Fax, Print, Scan

