
Epson AcuLaser C2800N A colori 2400 x 2400 DPI A4

Marchio: Epson Codice prodotto: C11CA09001BX

Nome del prodotto: AcuLaser C2800N





Printing		Performance	
Print speed (colour, normal quality, A4/US Letter) Colour * Print technology * Duplex printing *	20 ppm Laser	Internal memory * Maximum internal memory Processor frequency Sound pressure level (printing) Sound power level (standby)	128 MB 640 MB 400 MHz 30 dB 51 dB
Maximum resolution *	2400 x 2400 DPI	Design	
Print speed (black, normal quality, A4/US Letter) * Warm-up time	25 ppm 30 s	Certification	2006/95/EC EN60950-1, 2004/108/EC, EN 55022 Class B, EN 55024, EN 61000-3-2; EN 61000-3-3
Time to first page (black, normal)	15 s	Power	
Time to first page (colour, normal) Features	15 s	Power consumption (standby) Power consumption (PowerSave)	78 W 17 W
Maximum duty cycle *	60000 pages per month	Operational conditions	
Input & output capacity Total input capacity * Total output capacity * Multi-Purpose tray	250 sheets 250 sheets	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 32 °C 0 - 35 °C 10 - 85% 15 - 80%
Multi-Purpose tray input capacity Maximum input capacity	150 sheets 950 sheets	Sustainability	ENERGY OT A
Paper handling		Sustainability certificates	ENERGY STAR
Maximum ISO A-series paper size * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Media weight (tray 1)	A4 A4, A5 B5 Executive, Legal, Letter 60 - 216 gsm	Weight & dimensions Weight Dimensions (WxDxH) Other features	24 kg 408 x 577 x 477 mm
	00 - 210 gsm	Mac compatibility	(76.2. 220 mm) v (09.4. 255.6
Network		Standard media sizes	(76.2 - 220 mm) x (98.4 - 355.6 mm)
Network ready Supported network protocols (IPv4)	TCP/IP: LPR, FTP, IPP, PORT2501, PORT9100, TCP/IP, NetBEUI TCP/IP: SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, mDNS†1, SNTP, SSDP, SLP, Auto-IP, SSDP MS, SNMP	Power requirements	220V - 240V $\pm 10\%$ / 50Hz, 60Hz \pm 3Hz / 4.0 A
Management protocols		Networking features Power consumption (active) Compatible operating systems	Ethernet 10/100 Base-TX 730 W Windows 2000 / XP / Server 2003 / Vista / XP x64 Edition / Server 2003 x64 / Vista x64 Mac OS 10.2.810.4.X,10.4.X
		Emulations	ESC/P-C, PCL5c, PCL6, APS3, PDF1.3, ESCP2, FX, I239X
		Stand-by LED	✓

