DELL C7520QT 189.2 cm (74.5") 3840 x 2160 4K UHD LCD

** :** DELL

: DELL-C7520QT

** :** C7520QT

DELL C7520QT. : 189.2 cm (74.5"), : 3840 x 2160 , HD: 4K UHD, : LCD, : 8 ms, : 178°, : 178°. . USB, USB: 3.2 Gen 1 (3.1 Gen 1). VESA. :

Display		Ports & interfaces	
Display diagonal *	189.2 cm (74.5")	RS-232 ports	1
Display resolution *	3840 x 2160 pixels	**Network**	
HD type *	4K Ultra HD	Ethernet LAN	✔
Display technology *	LCD	**Ergonomics**	
Panel type *	IPS	VESA mounting *	✔
Backlight type	LED	Panel mounting interface	400 x 400 mm
Touchscreen *	✔	Wall mountable	✔
Touchscreen type	Multi-user	Cable lock slot *	✔
Touch technology	Multi-touch	Height adjustment *	✘
Number of simultaneous touchpoints	20	Picture-in-Picture	✔
Display brightness	350 cd/m²	**Power**	
Response time *	8 ms	Energy efficiency class (SDR) *	G
Screen shape *	Flat	Energy consumption (SDR) per 1000 hours *	140 kWh
Supported video modes	2160p	Power consumption (typical) *	140 W
Aspect ratio	16:9	Power consumption (standby) *	0.3 W
Contrast ratio (typical) *	1200:1	Power consumption (max)	270 W
Viewing angle, horizontal	178°	Power consumption (off)	0.3 W
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Display number of colours *	1.073 billion colours	AC input frequency	50 - 60 Hz
Pixel pitch	0.429 x 0.429 mm	Power supply type	AC
Viewable size diagonal	189.3 cm	Energy efficiency scale	A to G
Surface hardness	9H	**Operational conditions**	
Colour gamut	72%	Operating temperature (T-T)	0 - 40 °C
Anti-glare surface	✔	Storage temperature (T-T)	-20 - 60 °C
Performance		Operating relative humidity (H-H)	20 - 80%
NVIDIA G-SYNC *	✘		
AMD FreeSync *	✘		

Performance

Stylus pen hover function	✔

Multimedia

Number of speakers	2
RMS rated power	40 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design

Product colour *	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B
Number of upstream ports	3
Number of USB Type-B upstream ports quantity	3
USB Type-A downstream ports quantity	3
VGA (D-Sub) ports quantity	1
HDMI *	✔
HDMI ports quantity	3
HDMI version	2.0
DisplayPorts quantity	1
Audio input	3.5 mm
Audio output	3.5 mm

Operational conditions

Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12191 m

Weight & dimensions

Width (without stand)	1735 mm
Depth (without stand)	79.1 mm
Height (without stand)	1017.4 mm
Weight (without stand)	76 kg

Packaging content

Cables included	DisplayPort, HDMI, USB, VGA
Remote control included	✔
Stylus included	✔
Quick start guide	✔

Sustainability

Sustainability certificates	ENERGY STAR

Other features

Display viewable area (HxV)	1649.7 x 927.9 mm
Connection to PC	✔
Placement supported	Horizontal
Compliance certificates	RoHS
Ethernet LAN (RJ-45) ports	1
Certification	UL

Logistics data

Harmonized System (HS) code	85285210

0884116335702

884116335702