

Epson PowerLite Pro G5750WU 4500 3LCD WUXGA (1920x1200) 3D

Brand : Epson

Model : V11H345020

Series : PowerLite Pro G5750WU

Epson PowerLite Pro G5750WU. 3LCD 3D: 4500 ANSI lumens, 3LCD: LCD, 3LCD resolution: WUXGA (1920x1200). 3D: 3D, 3D: 2000 D, 3D: 3000 D. 3D: 3D, 3D: 21.28 - 37.94 mm, 3D: 1.65 - 2.55. 3D: 3D: NTSC, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM, 3D: 1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 640 x 480..., 3D: 1080i, 1080p, 480i, 480p, 576i, 576p, 720p. 3D: RS-232, USB: USB: USB: A



Projector		Ports & interfaces	
Screen size compatibility *	762 - 7620 mm (30 - 300")	Serial interface type *	RS-232
Projection distance	0 - 14.9 m	VGA (D-Sub) ports quantity *	1
Projector brightness *	4500 ANSI lumens	HDMI ports quantity *	1
Projection technology *	LCD	USB connector type	USB Type-A
Projector native resolution *	WUXGA (1920x1200)	BNC input ports	1
Contrast ratio (typical) *	1500:1	DVI port *	✓
Number of colours	16.78 million colours	Network	
Horizontal scan range	15 - 92 kHz	Ethernet LAN *	✓
Vertical scan range	50 - 85 Hz	Ethernet LAN (RJ-45) ports	1
Keystone correction, horizontal	-20 - 20°	Ethernet LAN data rates	100 Mbit/s
Keystone correction, vertical	-30 - 30°	Features	
Matrix type	3-panel (p-Si TFT active)	Noise level (economic mode)	33 dB
Light source		Dot clock scanning frequency	162 MHz
Light source type *	Lamp	Noise level *	39 dB
Service life of light source *	2000 h	Design	
Service life of light source (economic mode)	3000 h	Product colour *	White
Lamp type	UHE	Cable lock slot	✓
Lamp power	330 W	Cable lock slot type	Kensington
Lens system		Display	
Focus *	Manual	Built-in display *	✗
Focal length range	21.28 - 37.94 mm	Power	
Aperture range (F-F)	1.65 - 2.55	Power source *	AC
Zoom capability	✓	Power consumption (typical) *	477 W
Zoom type	Manual	Power consumption (standby) *	10 W
Optical zoom	1.x	AC input voltage	100 - 240 V
Throw ratio	1.3 - 2.36:1	AC input frequency	50 - 60 Hz
Horizontal lens shift range	-9 - 9°	Operational conditions	
Vertical lens shift range	-58 - 58°	Operating relative humidity (H-H)	0 - 40%
Video		Weight & dimensions	
Analog signal format system *	NTSC, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM	Width	45.3 mm
Full HD *	✗	Depth	30 mm
Supported graphics resolutions	1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 640 x 480 (VGA), 800 x 600 (SVGA)	Height	14.6 mm
		Weight *	6.8 kg

Video		Packaging content	
Supported video modes	1080i, 1080p, 480i, 480p, 576i, 576p, 720p	Remote control included *	×
Ports & interfaces		Other features	
S-Video inputs quantity	1	Aspect ratio	16:10
USB 2.0 ports quantity	1	RS-232 ports	1
		Security features	cable hole, lens lock, lock provision

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-APR-2025. Prints or copies of Information are only valid on the printed Publication date