



## Canon i-SENSYS MF8080Cw Laser A4 2400 x 600 DPI 12 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS

Product code: 5119B021

Product name : MF8080Cw

Canon i-SENSYS MF8080Cw. Teknologi cetak: Laser, Cetakan: Cetakan berwarna, Resolusi maksimum: 2400 x 600 DPI, Kelajuan cetak (warna, kualiti terbaik, A4/Surat AS): 8 ppm. Menyalin: Penyalinan berwarna, Resolusi salinan maksimum: 600 x 600 DPI. Imbasan: Pengimbasan berwarna, Resolusi imbasan optik: 600 x 600 DPI. Faks: Faks berwarna. Maximum ISO A-series paper size: A4. Wi-Fi. Product color: Putih



Printing		Paper handling	
Print resolution colour	600 x 600 DPI	Maximum ISO A-series paper size *	A4
Print technology *	Laser	Maximum print size	216 x 356 mm
Printing *	Colour printing	Paper tray media types *	Coated paper, Envelopes, Labels, Plain paper, Recycled paper, Transparencies
Duplex printing *	✗	ISO A-series sizes (A0...A9) *	A4, A5
Maximum resolution *	2400 x 600 DPI	ISO B-series sizes (B0...B9)	B5, B6
Print speed (black, normal quality, A4/US Letter) *	12 ppm	Non-ISO print media sizes	Executive, Statement
Print speed (colour, normal quality, A4/US Letter)	8 ppm	Envelopes sizes	10, B5, C5, DL
Warm-up time	30 s	Custom media width	76.2 - 215.9 mm
Time to first page (black, normal)	22 s	Custom media length	127 - 356.6 mm
Time to first page (colour, normal)	28.5 s	Paper tray media weight	60 - 220 g/m <sup>2</sup>
Copying		Auto Document Feeder (ADF) media weight	50 - 105 g/m <sup>2</sup>
Duplex copying *	✗	<b>Ports &amp; interfaces</b>	
Copying *	Colour copying	Standard interfaces	Ethernet, USB 2.0, Wireless LAN
Maximum copy resolution *	600 x 600 DPI	Direct printing *	✗
Copy speed (black, normal quality, A4)	12 cpm	USB port	✓
Copy speed (colour, normal quality, A4)	8 cpm	<b>Network</b>	
Maximum number of copies	99 copies	Wi-Fi *	✓
Copier resize	25 - 400%	Ethernet LAN *	✓
Scanning		Wi-Fi standards	802.11b, 802.11g
Duplex scanning *	✗	<b>Performance</b>	
Scanning *	Colour scanning	Card reader integrated	✗
Optical scanning resolution *	600 x 600 DPI	Internal memory *	128 MB
Maximum scan resolution	9600 x 9600 DPI	Sound pressure level (printing)	63.4 dB
Maximum scan area	216 x 355 mm	Sound pressure level (copying)	63.4 dB
Image formats supported	JPG, TIF	Sound pressure level (scanning)	63.4 dB
Input colour depth	24 bit	Sound power level (standby)	43 dB
Output colour depth	24 bit	Mac compatibility	✓
Greyscale levels	256	<b>Design</b>	
Fax		Product colour *	White
Duplex faxing	✗	Market positioning *	Business
Faxing *	Colour faxing	Built-in display *	✓
Fax resolution (black)	200 x 100 DPI	Display	LCD
Fax transmission speed	3 sec/page		
Modem speed	33.6 Kbit/s		

<b>Fax</b>		<b>Power</b>	
Fax memory	512 pages	Power consumption (average operating)	900 W
Auto-redialing	✓	Power consumption (standby)	15 W
Fax speed dialing (max numbers)	181	AC input voltage	220 - 240 V
Fax forwarding	✓	AC input frequency	50 - 60 Hz
Fax broadcasting	210 locations	<b>Operational conditions</b>	
Error Correction Mode (ECM)	✓	Operating relative humidity (H-H)	20 - 80%
Fax dual access	✓	Operating temperature (T-T)	10 - 30 °C
<b>Features</b>		<b>Weight &amp; dimensions</b>	
Maximum duty cycle *	30000 pages per month	Width	430 mm
Digital sender	✗	Depth	484 mm
Number of print cartridges *	4	Height	429 mm
Printing colours *	Black, Cyan, Magenta, Yellow	Weight	26 kg
Page description languages	UFRII-LT	<b>Packaging content</b>	
<b>Input &amp; output capacity</b>		Drivers included	✓
Total input capacity *	150 sheets	<b>Other features</b>	
Total output capacity *	125 sheets	Networking features	Fast Ethernet, WLAN
Paper input type	Cassette	Dimensions (WxDxH)	430 x 484 x 429 mm
Auto document feeder (ADF)	✓	Network ready	✓
Auto document feeder (ADF) input capacity	50 sheets	Compatible operating systems	Windows 2000, Server 2003, Server 2008, Server 2008 R2, Windows XP, Windows Vista, Windows 7, Mac OS X 10.4.9- 10.7.x, Linux
		All-in-one functions	Copy, Fax, Print, Scan
		Colour all-in-one functions	Copy, Fax, Print, Scan

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date