

Fujitsu PRIMERGY TX200 S3 server Tower (4U) Intel® Xeon® 5000 reeks 5110 1,6 GHz 1 GB DDR2-SDRAM 600 W

Merk : Fujitsu

Productfamilie: PRIMERGY

Artikelcode: VFY:TX200S3-002DE



Productnaam : PRIMERGY TX200 S3

Fujitsu PRIMERGY TX200 S3. Processorfamilie: Intel® Xeon® 5000 reeks, Frequentie van processor: 1,6 GHz, Processormodel: 5110. Intern geheugen: 1 GB, Intern geheugentype: DDR2-SDRAM, Geheugenlayout: 2 x 0.5 GB. Soort optische drive: DVD-ROM. Netvoeding: 600 W. Type behuizing: Tower (4U)

| Processor | | Software | |
|---|---|---|---|
| Processor manufacturer * Processor family * Processor model * Processor cores Processor cache Motherboard chipset Thermal Design Power (TDP) Processor cache type Processor front side bus Processor front side bus Processor lithography Processor threads Processor operating modes FSB Parity Bus type | Intel Intel® Xeon® 5000 Sequence 5110 1.6 GHz 2 4 MB Intel® 5000V 65 W L2 1066 MHz LGA 771 (Socket J) 65 nm 2 64-bit ✓ FSB | Compatible operating systems * | Microsoft Windows 2000 Server, Microsoft Windows 2000 Advanced Server, Microsoft Windows Server 2003 Enterprise Edition, Microsoft Windows Server 2003 Web Edition, Microsoft Windows Server 2003 Standard Edition, Microsoft Windows Small Business Server 2003 Standard Ed, Microsoft Windows Small Business Server 2003 Premium Ed, SuSE Linux Enterprise Server 8 for Intel x86, Red Hat Enterprise Linux 3, SuSE Linux Enterprise Server 9 - x86/AMD64/Intel EM64T, Microsoft Windows Server 2003 Standard x64 Edition, Red Hat Enterprise Linux 4, Microsoft Windows Server 2003 Enterprise x64 Edition, SuSE Linux 9.2, SuSE Linux 9.3, Red Hat Enterprise Linux 4 - Intel EM64T |
| Processor codename | Woodcrest | Bundled software | ServerStart, ServerView |
| Tcase | 65 °C | Processor special features | |
| ECC supported by processor | × | Intel Rapid Storage Technology | × |
| Execute Disable Bit | ✓ | Enhanced Intel SpeedStep | 1 |
| Idle States | <i>✓</i> | Technology Intel® Wireless Display (Intel® | |
| Thermal Monitoring Technologies | ✓ | WiDi) | × |
| Processor package size | 37.5 x 37.5 mm | Intel Virtualization Technology for | × |
| Embedded options available | × | Directed I/O (VT-d) | ^ |
| Number of Processing Die Transistors | 291 M | Intel® Anti-Theft Technology (Intel® AT) | × |
| CPU multiplier (bus/core ratio) Processing Die size | 6 143 mm² | Intel® Hyper Threading Technology (Intel® HT Technology) | × |
| Processor series | Intel Xeon 5100 Series | Intel® My WiFi Technology (Intel® MWT) | × |
| Conflict-Free processor | × | Intel® Turbo Boost Technology | × |
| Memory | | Intel® Quick Sync Video Technology | × |
| Internal memory * | 1 GB | Intel® InTru [™] 3D Technology | × |
| Internal memory type * ECC | DDR2-SDRAM | Intel® Clear Video HD Technology (Intel® CVT HD) | × |
| Memory layout (slots x size) | 2 x 0.5 GB | Intel® Insider™ | × |
| Maximum internal memory * | 16 GB | Intel Flex Memory Access | × |
| Storage | | Intel® AES New Instructions (Intel® | × |
| RAID levels | 1 | AES-NI) | |

| Storage | | Processor special features | |
|---|------------------|---|--|
| Optical drive type * | DVD-ROM | Intel Trusted Execution Technology | × |
| Network | | Intel Enhanced Halt State | 1 |
| Networking features | Gigabit Ethernet | Intel VT-x with Extended Page Tables (EPT) | × |
| Ports & interfaces | | Intel Demand Based Switching | × |
| Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity PS/2 ports quantity VGA (D-Sub) ports quantity | 1 3 2 1 | Intel Clear Video Technology | × |
| | | Intel [®] Clear Video Technology for Mobile Internet Devices (Intel CVT for MID) | × |
| Serial ports quantity | 2 | Intel 64 | 1 |
| Design | | Intel Virtualization Technology (VT- x) | Image: A second s |
| Chassis type * | Tower (4U) | Intel Dual Display Capable Technology | × |
| | | Intel FDI Technology | × |
| | | Intel Fast Memory Access | × |
| | | Processor ARK ID | 27214 |
| | | Power | |
| | | Power requirements Power supply * | 100 - 240 VAC, 50 - 60 Hz 600 W |
| | | Weight & dimensions | |

Width

Depth

Height

Weight

Other features Storage drive controller

CD read speed

Dimensions (WxDxH)

286 mm

775 mm

473 mm

25 kg

SAS

48x

286 x 775 x 473 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.