Epson AcuLaser C2800DTN

Merk: Epson Artikelcode: C11CA09031BY

Productnaam: Epson AcuLaser C2800DTN

Betrouwbare kleurenlaserprint voor uw bedrijf

Epson AcuLaser C2800DTN. Printtechnologie: Laser, Kleur. Gebruiksindicatie (maximaal): 60000 pagina's per maand. Maximale resolutie: 2400 x 2400 DPI, Printsnelheid (zwart, standaardkwaliteit, A4/US Letter): 25 ppm, Duplex printen. Netwerkgereed





Printing		Power	
Print speed (colour, normal quality, A4/US Letter)	lity, 20 ppm	Power consumption (standby) Power consumption (PowerSave)	78 W 17 W
Colour *	✓	Operational conditions	
Print technology *	Laser	Operating temperature (T-T) 10 - 32 °C	10 22 %
Duplex printing *	✓	Storage temperature (T-T)	0 - 35 °C
Maximum resolution *	2400 x 2400 DPI	Operating relative humidity (H-H)	10 - 85%
Print speed (black, normal quality, A4/US Letter) *	25 ppm	Storage relative humidity (H-H)	15 - 80%
Warm-up time	30 s	Sustainability	
Time to first page (black, normal)	15 s	Sustainability certificates	ENERGY STAR
Time to first page (colour, normal)	15 s	Weight & dimensions	
Features		Weight	32.9 kg
Maximum duty cycle * Country of origin	60000 pages per month China	Dimensions (WxDxH)	408 x 577 x 615 mm
		Packaging data	
Input & output capacity		Package width	570 mm
Total input capacity *	400 sheets	Package depth	740 mm
Total output capacity *	250 sheets	Package height	840 mm
Paper tray 2 input capacity	550 sheets	Package weight	43.9 kg
Multi-Purpose tray	✓	Logistics data	
Multi-Purpose tray input capacity	150 sheets	Pallet gross width	120 cm
Maximum input capacity	950 sheets	Pallet gross height	100 cm
Paper handling		Products per pallet layer	2 pc(s)
Media weight (tray 1)	60 - 216 g/m²	Products per pallet	4 pc(s)
		Pallet length (UK)	2.33 m

Network		Logistics data	
Network ready	✓	Products per pallet layer (UK)	2 pc(s)
Supported network protocols (IPV4)	LPR, FTP, IPP, PORT2501, PORT9100, TCP/IP, NetBEUI SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, mDNS†1, SNTP, SSDP, SLP, Auto-IP, SSDP MS, SNMP	Products per pallet (UK)	4 pc(s)
		Other features	
Management protocols		Mac compatibility	✓
		Standard media sizes	A4, A5, B5, LT, GLT, HLT, LGL, GLG ISO - B5, EXE, C5, DL (76.2 - 220 mm) x (98.4 - 355.6 mm)
Performance		Power requirements	220V - 240V, 50Hz, 60Hz
Internal memory *	128 MB	Networking features	Ethernet 10 / 100 Base-TX
Maximum internal memory	640 MB 400 MHz 30 dB 51 dB	Power consumption (active)	750 W
Processor frequency Sound pressure level (printing) Sound power level (standby)		Compatible operating systems	Windows 2000 / XP / Server 2003 / Vista / XP x64 Edition / Server 2003 x64 / Vista x64, Mac OS X
Design		Emulations	ESC/P-C, PCL5c, PCL6, APS3, PDF1.3, ESCP2, FX, I239X
Certification	2006/95/EC EN60950-1 2004/108/EC, EN 55022 Class B, EN 55024, EN 61000-3-2; EN 61000-3-3	Quantity per pack	1 pc(s)

