
Epson PowerLite Pro G5750WU 4500 ANSI lumens LCD WUXGA (1920x1200) Branco

Marca : Epson Código do produto: V11H345020

Nome do produto: PowerLite Pro G5750WU







Projector		Ports & interfaces	
Screen size compatibility * Projection distance Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) *	762 - 7620 mm (30 - 300") 0 - 14.9 m 4500 ANSI lumens LCD WUXGA (1920x1200) 1500:1 16.78 million colours 15 - 92 kHz 50 - 85 Hz -20 - 20° -30 - 30°	Serial interface type * VGA (D-Sub) ports quantity * HDMI ports quantity * USB connector type BNC input ports DVI port *	RS-232 1 1 USB Type-A 1
Number of colours Horizontal scan range		Network	
/ertical scan range 50 (eystone correction, horizontal -20		Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates	1 100 Mbit/s
Matrix type	3-panel (p-Si TFT active)	Features	
Light source Light source type * Service life of light source *	Lamp 2000 h	Noise level (economic mode) Dot clock scanning frequency Noise level *	33 dB 162 MHz 39 dB
Service life of light source	3000 h	Design	
(economic mode) Lamp type Lamp power	UHE 330 W	Product colour * Cable lock slot Cable lock slot type	White ✓ Kensington
Lens system		,,	Kensington
Focus * Focal length range	Manual 21.28 - 37.94 mm	Display Built-in display *	×
Aperture range (F-F)	1.65 - 2.55	Power	
Zoom capability Zoom type Optical zoom Throw ratio Horizontal lens shift range	Manual 1.x 1.3 - 2.36:1 -9 - 9°	Power source * Power consumption (typical) * Power consumption (standby) * AC input voltage AC input frequency	AC 477 W 10 W 100 - 240 V 50 - 60 Hz
Vertical lens shift range	-58 - 58°	Operational conditions	
Video	NTCC NTCC 4 42 DAL DAL CO DAL	Operating relative humidity (H-H)	0 - 40%
Analog signal format system *	NTSC, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM	Weight & dimensions	
Full HD * Supported graphics resolutions	X 1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 640 x 480 (VGA), 800 x 600 (SVGA)	Width Depth Height Weight *	45.3 mm 30 mm 14.6 mm 6.8 kg

Video		Packaging content	
Supported video modes	1080i, 1080p, 480i, 480p, 576i, 576p, 720p	Remote control included *	x
Ports & interfaces		Other features	
S-Video inputs quantity USB 2.0 ports quantity	1	Aspect ratio RS-232 ports Security features	16:10 1 cable hole, lens lock, lock provision

