
Epson PowerLite Pro G5750WU 4500 ANSI lumens LCD WUXGA (1920x1200) Alb

Marcă : Epson Codul produsului: V11H345020

Nume produs: PowerLite Pro G5750WU







Draiostor		Darta C interferes	
Projector Screen size compatibility * Projection distance Projector brightness * Projection technology * Projector native resolution *	762 - 7620 mm (30 - 300") 0 - 14.9 m 4500 ANSI lumens LCD WUXGA (1920x1200)	Ports & interfaces Serial interface type * VGA (D-Sub) ports quantity * HDMI ports quantity * USB connector type BNC input ports	RS-232 1 1 USB Type-A
Contrast ratio (typical) * Number of colours	1500:1	DVI port *	✓
Horizontal scan range Vertical scan range Keystone correction, horizontal Keystone correction, vertical	range 15 - 92 kHz range 50 - 85 Hz rection, horizontal -20 - 20° rection, vertical -30 - 30°	Network Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates	1 100 Mbit/s
Matrix type	3-panel (p-Si TFT active)	Features	
Light source Light source type * Service life of light source *	Lamp 2000 h	Noise level (economic mode) Dot clock scanning frequency Noise level *	33 dB 162 MHz 39 dB
Service life of light source	3000 h	Design	
(economic mode) Lamp type Lamp power	UHE 330 W	Product colour * Cable lock slot Cable lock slot type	White ✓ Kensington
Lens system	Marcal Control	Display	
Focal length range	Manual 21.28 - 37.94 mm	Built-in display *	×
Aperture range (F-F)	1.65 - 2.55	Power	
Zoom capability Zoom type Optical zoom Throw ratio Horizontal lens shift range Vertical lens shift range	Manual 1.x 1.3 - 2.36:1 -9 - 9° -58 - 58°	Power source * Power consumption (typical) * Power consumption (standby) * AC input voltage AC input frequency	AC 477 W 10 W 100 - 240 V 50 - 60 Hz
Video	••	Operational conditions	
Analog signal format system *	NTSC, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM	Operating relative humidity (H-H) Weight & dimensions	0 - 40%
Full HD * Supported graphics resolutions	X 1280 x 1024 (SXGA), 1400 x 1050 (SXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 640 x 480 (VGA), 800 x 600 (SVGA)	Width Depth Height Weight *	45.3 mm 30 mm 14.6 mm 6.8 kg

Video		Packaging content	
Supported video modes	1080i, 1080p, 480i, 480p, 576i, 576p, 720p	Remote control included *	x
Ports & interfaces		Other features	
S-Video inputs quantity USB 2.0 ports quantity	1	Aspect ratio RS-232 ports Security features	16:10 1 cable hole, lens lock, lock provision

