EPSON'

Epson Aculaser C2800DTN + Duplex Unit □ 2400 x 2400 DPI

Brand: Epson **Product code**: C11CA09031BY

Product name : Aculaser C2800DTN + Duplex Unit





Printing		Power	
Print speed (colour, normal quality, A4/US Letter)	20 ppm ✓ Laser ✓ 2400 x 2400 DPI	Power consumption (standby) Power consumption (PowerSave)	78 W 17 W
Colour *		Operational conditions	
Print technology * Duplex printing * Maximum resolution * Print speed (black, normal quality, A4/US Letter) *		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 32 °C 0 - 35 °C 10 - 85% 15 - 80%
Warm-up time	30 s	Sustainability	
Time to first page (black, normal) 15 s Time to first page (colour, normal) 15 s		Sustainability certificates	ENERGY STAR
	15 s	Weight & dimensions	
Features		Weight	32.9 kg
Maximum duty cycle *	60000 pages per month	Dimensions (WxDxH)	408 x 577 x 615 mm
Country of origin	China	Packaging data	
Input & output capacity Total input capacity * 400 sheets Total output capacity * 250 sheets Paper tray 2 input capacity 550 sheets	250 sheets	Package width Package depth Package height Package weight	570 mm 740 mm 840 mm 43.9 kg
Multi-Purpose tray	✓	Logistics data	
Multi-Purpose tray input capacity Maximum input capacity	150 sheets 950 sheets	Pallet gross width Pallet gross height	120 cm 100 cm
Paper handling		Products per pallet layer	2 pc(s)
Media weight (tray 1)	60 - 216 g/m²	Products per pallet Pallet length (UK)	4 pc(s) 2.33 m

Network		Logistics data	
Network ready	✓	Products per pallet layer (UK)	2 pc(s)
Supported network protocols (IPv4)	LPR, FTP, IPP, PORT2501, PORT9100, TCP/IP, NetBEUI SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS,	Products per pallet (UK)	4 pc(s)
		Other features	
Management protocols BOOTP, APIPA, PING, DDNS, mDNS†1, SNTP, SSDP, SLP, Auto-IP, SSDP MS, SNMP		Mac compatibility	✓
	Standard media sizes	A4, A5, B5, LT, GLT, HLT, LGL, GLG ISO - B5, EXE, C5, DL (76.2 - 220 mm) x (98.4 - 355.6 mm)	
Performance		Power requirements	220V - 240V, 50Hz, 60Hz
Internal memory *	128 MB	Networking features	Ethernet 10 / 100 Base-TX
Maximum internal memory	640 MB 400 MHz 30 dB 51 dB	Power consumption (active)	750 W
Processor frequency Sound pressure level (printing) Sound power level (standby)		Compatible operating systems	Windows 2000 / XP / Server 2003 / Vista / XP x64 Edition / Server 2003 x64 / Vista x64, Mac OS X
Design		Emulations	ESC/P-C, PCL5c, PCL6, APS3, PDF1.3, ESCP2, FX, I239X
Certification	2006/95/EC EN60950-1 2004/108/EC, EN 55022 Class B, EN 55024, EN 61000-3-2; EN 61000-3-3	Quantity per pack	1 pc(s)

