Canon

Canon i-SENSYS MF8550Cdn Ⅲ A4 1200 x 1200 DPI 20 ppm

: Canon : i-SENSYS :: 6849B034

____: MF8550Cdn





Printing		Features	
Duplex printing mode	Auto	Number of printer fonts	45
Print technology *	Laser	Input & output capacity	
Printing *	Colour printing	Total number of input trays *	3
Duplex printing *	✓	Total input capacity *	250 sheets
Maximum resolution *	1200 x 1200 DPI	Total output capacity *	125 sheets
Print speed (black, normal quality, A4/US Letter) *	20 ppm	Multi-Purpose tray	✓
Print speed (colour, normal quality, A4/US Letter)	20 ppm	Multi-Purpose tray input capacity Auto document feeder (ADF)	50 sheets
Warm-up time	23 s	Auto document feeder (ADF) input	50 sheets
Time to first page (black, normal) Time to first page (colour, normal)	14.5 s 14.5 s	capacity Maximum number of input trays	4
Print margins (top, bottom, right, left)	5 mm	Paper handling	
Economical printing	/	Maximum ISO A-series paper size *	A4
. 5	•	Maximum print size	216 x 297 mm
Copying Duplex copying * Copying *	✓ Colour copying	Paper tray media types *	Coated paper, Envelopes, High resolution paper, Labels, Plain paper, Recycled paper, Transparencies
Maximum copy resolution *	600 x 600 DPI	ISO A-series sizes (A0A9) *	A4, A5
Copy speed (black, normal quality, A4)	20 cpm	ISO B-series sizes (B0B9)	B5
Copy speed (colour, normal quality, A4)	20 cpm	Non-ISO print media sizes Envelopes sizes	Executive, Statement 10, B5, C5, DL
Time to first copy (black, normal)	15.5 s	Custom media width	128 - 139.7 mm
Time to first copy (colour, normal)	16.2 s	Custom media length	215.9 - 355.6 mm
Maximum number of copies	99 copies	Paper tray media weight	60 - 220 g/m²
Copier resize	25 - 400%	Auto Document Feeder (ADF) media weight	50 - 105 g/m²
Scanning		Ports & interfaces	
Scanning * Optical scanning resolution *	Colour scanning 600 x 600 DPI	Standard interfaces	Ethernet, USB 2.0

Scanning		Ports & interfaces	
	9600 x 9600 DPI ADF scanner File, Image, USB JPG, TIF PDF 24 bit 24 bit 256 TWAIN, WIA	Direct printing *	✓
		USB port	✓
		Network	
		Wi-Fi *	×
		Ethernet LAN *	···
		Mobile printing technologies	Apple AirPrint, Google Cloud Print
		Performance	
Fax		Card reader integrated Internal memory *	X 512 MB
	✓	Sound pressure level (printing)	50.3 dB
	400 x 400 DPI 3 sec/page	Design	30.5 4.5
		Product colour *	Black
Modem speed	33.6 Kbit/s	Market positioning *	Business
Fax memory	512 pages	Built-in display *	✓
Auto-redialing	√	Display	LCD
Fax speed dialing (max numbers)	181	Display diagonal	8.89 cm (3.5")
Fax forwarding	ng 210 locations	Display number of lines	7 lines
Fax broadcasting Error Correction Mode (ECM)		Power	
Fax dual access	·	Power consumption (average	1200 W
	•	operating)	
Features		Power consumption (standby)	23 W
Maximum duty cycle *	40000 pages per month	Power consumption (off) AC input voltage	1 W 220 - 240 V
Printing colours * Page description languages	Black, Cyan, Magenta, Yellow PCL 5c, PCL 6, UFRII-LT	AC input voitage AC input frequency	50 - 60 Hz
		Sustainability	30 00 112
		Sustainability certificates	ENERGY STAR
		•	ENERGI SIAK
		Weight & dimensions	
		Width	430 mm
		Depth Height	484 mm 479 mm
		Weight	31 kg
		Traight	5± Ng

